



AURATM
PERFORMANCE HEATERS

SHADOW

S E R I E S

NO-LIGHT
RADIANT HEATER



DS15120B – Black
up to 1500W / 120V only

DS24240B – Black
up to 2400W / 240V only

DS3208B / DS32240B – Black
up to 3200W / 208V & 240V



SHADOW | SERIES

Aura Shadow	Power	Voltage	Current	BTU	Min Mount Height	Ceiling Clearance		Sidewall Clearance	Certification
						Bracket Direct	Wall Mounted		
DS32208B Black	3200W	208V	15.4A	10,920 btu	79 inch (2100 cm) US 96 inch (2400 cm) CDN	4 inch (10 cm)	8 inch (20 cm)	18 inch (46 cm)	cETLus (UL2021/CSA22.2)
DS32240B Black	3200W	240V	13.3A	10,920 btu	79 inch (2100 cm) US 96 inch (2400 cm) CDN	4 inch (10 cm)	8 inch (20 cm)	18 inch (46 cm)	cETLus (UL2021/CSA22.2)
DS24240B Black	2400W	240V	10A	8,200 btu	79 inch (2100 cm) US 96 inch (2400 cm) CDN	4 inch (10 cm)	8 inch (20 cm)	18 inch (46 cm)	cETLus (UL2021/CSA22.2)
DS15120B Black	1500W	120V	12.5A	5100 btu	79 inch (2100 cm) US 96 inch (2400 cm) CDN	4 inch (10 cm)	8 inch (20 cm)	18 inch (46 cm)	cETLus (UL2021/CSA22.2)

240V heaters are not recommended to be de-rated to 208V.

NO LIGHT RADIANT HEATER FOR USE IN ENCLOSED OR SEMI-ENCLOSED OUTDOOR SPACES IN MODERATE CLIMATES. INSTALLER, SPECIFIER OR ENGINEER SHOULD TARGET 8' MOUNTING HEIGHT TO BOTTOM OF HEATER FOR OPTIMAL PERFORMANCE.

Aura™ Performance Heaters is a registered trademark of Inforesight Consumer Products Inc.

Toll Free 866-321-8373 International Customers + 001-905-568-7655 General Inquiries / Sales Support / Distributor Inquiries: info@auraheaters.com